



IBC Advanced Alloys

MATERIAL SAFETY DATA SHEET

Date Issued: April 13, 2010

1. PRODUCT AND COMPANY IDENTIFICATION: This material data sheet (MSDS) provides information on a specific group of manufactured metal products. As these metal alloy products share a common physical nature and constituents, the data presented are applicable to all alloys identified.

This MSDS identifies the following alloys: **C10100, C10700, C10800 and C11000**

MANUFACTURER:

IBC ADVANCED ALLOYS, INC. NONFERROUS DIVISION; 401 Arvin Road, P. O. Box 349; Franklin, IN 46131

ON THE WEB: www.ibcadvancedalloys.com

EMERGENCY PHONE NUMBERS: 1-800-423-5612

2. HAZARD IDENTIFICATION AND POTENTIAL HEALTH EFFECTS

ELEMENT

CAS#

OSHA / P. E. L. ⁽¹⁾

COPPER (Cu) ⁽⁴⁾

7440-50-8

1.0 dust & mists, 0.1 fume

- Dust and fumes from melting, grinding and cutting may present a potential health hazard. Fumes may cause a metal fume fever with flu-like symptoms and damage or ulceration of the nasal passages. There may also be skin and hair discoloration. Dermatitis due to sensitization may occur in some individuals.

SILVER (Ag)

7740-22-4

0.01 silver metal

- Exposure to high levels of silver in the air has resulted in breathing problems, lung and throat irritation, and stomach pains. Skin contact with silver can cause mild allergic reactions such as rash, swelling, and inflammation in some people.

ARSENIC: (As)⁽⁴⁾⁽⁵⁾

7440-38-2

10 ug inorganic

- May cause irritation to the skin and mucous membranes. Gastrointestinal, nervous system, kidney and liver disorders have been reported in acute or chronic overexposures. Depression of bone marrow may also occur. Ingestion is harmful and may cause nausea, vomiting, paralysis, gastrointestinal irritation and may be fatal.

ANTIMONY: (Sb)

7440-36-0

0.5 dust, 0.5 fume

- May cause irritation to the skin and mucous membranes. Symptoms include metallic taste in the mouth, vomiting, colic, loss of appetite and weight, and diarrhea. In acute poisoning there may be death from circulatory or respiratory failure or toxic hepatitis. A skin/contact dermatitis may result which starts as an inflammation of the hair follicles and can progress through pus formation and sloughing to leave a contracted scar.

PHOSPHORUS(P)**7723-14-0****0.1 phosphorus**

- Phosphorus exists in several allotropic forms including white (or yellow), red, and black (or violet). White phosphorus has two modifications. Ordinary phosphorus is a waxy white solid but when pure, it is colourless and transparent. It is insoluble in water, but soluble in carbon disulphide. It catches fire spontaneously in air, when exposed to sunlight, or when heated in its own vapour to 250°C, it is converted to the red variety. This form does not ignite spontaneously and it is a little less dangerous than white phosphorus..

TELLURIUM (Te)**12494-80-9****0.1 tellurium**

- Tellurium is a dark-gray to brown amorphous powder or grayish-white, brittle solid. Exposure can irritate skin, eyes, nose and throat. Higher exposures can cause fluid buildup in the lungs with severe shortness of breath. Repeated exposure can cause odor to breath, nausea, vomiting and loss of appetite

OXYGEN (O)**7782-44-7****No PEL for Oxygen**

- Cough; dizziness; sore throat; visual disturbances at very high concentrations. At 100% oxygen for more than 24 hours: symptoms above plus weakness, fatigue, pain in joints and muscles, numbness and tingling in arms and legs, palpitations, headache, nasal congestion, ear disturbances, nausea, vomiting, loss of appetite, fever and swelling of mucous membranes. On contact with liquid: freezing burns.

(1) Permissible Exposure Limits are expressed in milligrams per cubic meter of air (mg/m³), unless noted.

(2) ug = microgram (one millionth of a gram; 10⁻⁶ gram)

(3) CL = Ceiling limit, not to be exceeded

(4) Is listed as a toxic chemical and requires reporting under Section 313 of the Community Right-To-Know Act.

(5) Item is suspected carcinogens in humans.

3. COMPOSITION/INFORMATION ON INGREDIENTS

UNS #	Description	Cu	Ag	As	Sb	P	Te	O
C10100(1)	OFE-Oxygen Free Electronic	99.99 min	-	0.0005	0.0004	0.0003	0.0002	0.0005
C10700	OFS-Oxygen Free w/Silver	99.95 min(2)	0.085	-	-	-	-	0.0010
C10800	OFS-Oxygen Free Low Phos.	99.95 min(3)	-	-	-	0.005-0.012	-	-
C11000	ETP-Electrolytic Tough Pitch	99.90 min (2)	-	-	-	-	-	- (4)

(1) Cu+Ag+As+Sb+P+Te+Zr, 99.9% min. (2) Ni+Co, 0.20% min.; Ni+Fe+Co, 0.6% max. (3) includes Co

(4) Cu+Sum of Named Elements, 99.5% min. (5) Cu+Sum of Named Elements, 99.7% min.

4. ACUTE HEALTH HAZARDS/FIRST AID MEASURES

ROUTES OF EXPOSURE: Direct eye or skin contact with metal dust or particles, and breathing metal fume or dust.

SYMPTOMS: Eye or skin particulate contact may cause irritation.

CONTACT WITH EYES: Metal particles should be removed by trained individuals such as a nurse or physicians

MEDICAL CONDITIONS EXAGGERATED BY OVEREXPOSURE: Allergy (sensitivity) to copper.

INGESTION: Induce vomiting immediately as directed by medical personnel.

CONTACT WITH SKIN: Use a mild hand cream if irritation develops.

INHALATION: Breathing dust or fume may cause nose and throat irritation and a sweet or metallic taste. Breathing high levels of fumes may cause metal fume fever which has flu-like symptoms. Copper, manganese or nickel exposure may cause asthma- like symptoms or skin rashes or dermatitis in people sensitive (allergic) to these metals.

Move to fresh air if overexposed to fumes.

5. FIRE FIGHTING MEASURES

- Metal solids will not burn or explode; however, finely divided metal dust can form explosive mixture in air.
- Explosive mixtures can form in areas with high concentrations of dust such as in process vessels, dust collectors and bulk loading operations.
- In case of a fire, isolate the fire and use class "D" fire extinguishing materials such as Lith-X, Dry Graphite, etc.
- DO NOT use water to extinguish fires around operations involving molten metal due to the potential for steam explosions.

6. ACCIDENTAL RELEASE

- If this material is a particulate, establish a restricted entry zone based on the severity of the spill. If dust or fume is collected and spilled, respiratory protection, dust masks or cartridge respirators with high efficiency particulate air filtration (HEPA) and protective clothing appropriate for the severity of the release should be used in cleaning up the spill.
- Clean up spills with a vacuum system utilizing a high efficiency particulate air (HEPA) filtration system followed by wet cleaning methods.
- Caution should be used to minimize airborne generation of particulates and avoid contamination of air and water.

7. HANDLING AND STORAGE

HAND AND BODY PROTECTION: Particulates may enter the body through cuts, abrasions or other wounds on the surface of the skin. Use appropriate work gloves when handling castings. Use protective apron and gauntlets if arc-air gouging, cutting or welding this material.

STORAGE: Store in a dry area.

8. EXPOSURE CONTROLS, PERSONAL PROTECTIVE EQUIPMENT

8.1 VENTILATION:

- Use sufficient ventilation to keep concentrations of dust and fumes below safe exposure guidelines (TWA / PEL). Whenever possible, the use of local exhaust ventilation or other engineering controls is the preferred method of controlling exposure to airborne particulate.
- Where utilized, exhaust inlets to the ventilation system should be positioned as close as possible to the source of airborne generation. Avoid disruption of the airflow in the area of a local exhaust inlet by equipment such as a man-cooling fan. Check ventilation equipment regularly to ensure it is functioning properly. Provide training on the use and operation of ventilation to all users.

8.2 RESPIRATORS: If safe exposure guidelines are not met, use approved respirators for dusts or fumes; see OSHA Standards for Industry, 29 CFR 1910.134 for Respiratory Protection Program requirements.

8.3 EYE PROTECTION: Wear safety glasses, goggles, face shield, hood or welder's helmet when risk of eye injury is present, particularly during melting, casting, machining, grinding, welding, powder handling, etc. See OSHA Standards for Industry, 29 CFR 1910.133 for Eye and Face Protection Program requirements.

8.4 HEARING PROTECTION: Wear hearing protection if noise levels are at or above 90 dBA. See OSHA Standards for Industry, 29 CFR 1910.95 for Hearing Conservation Program requirements.

8.5 WORK PRACTICES:

- Develop work practices and procedures that prevent particulate from coming in contact with worker skin, hair, or personal clothing. Provide appropriate cleaning/washing facilities.
- Procedures should be written that clearly communicate the facility's requirements for protective clothing and personal hygiene. These clothing and personal hygiene requirements help keep particulate from being spread to non-production areas or from being taken home by the worker.
- Fabrication processes may leave a residue of particulate on the surface of parts, products or equipment that could result in employee exposure during subsequent material handling activities. As necessary, use vacuum systems with high efficiency particulate air (HEPA) filters to clean loose particulate from parts between processing steps.
- Do not use compressed air, brooms or conventional vacuum cleaners to remove particulate from surfaces as this activity can result in elevated exposures to airborne particulate. As a standard hygiene practice, always wash hands before eating or smoking.

8.6 OTHER PROTECTIVE EQUIPMENT:

- Protective over garments or work clothing should be worn by persons who may come in contact with particulates during activities such as machining, furnace rebuilding, air cleaning equipment filter changes, maintenance, furnace tending, etc.
- Contaminated work clothing and over garments must be managed in a controlled manner to prevent secondary exposure to workers of third parties, to prevent the spread of particulates to other areas, and to prevent particulate from being taken home by workers. This would include protective gloves and the correct eye protection determined by the exposure.

9. PHYSICAL AND CHEMICAL PROPERTIES:

APPEARANCE: Solid Metal

COLOR: Red

ODOR: No odor

MELTING POINT (°F) 1590°F - 1976°F

WATER SOLUBILITY: Not Soluble

SPECIFIC GRAVITY: 8.26 – 8.89

BOILING POINT: N/A

EVAPORATION RATE: N/A

VAPOR DENSITY: N/A

VAPOR PRESSURE: N/A

10: STABILITY AND REACTIVITY

General Reactivity

The material is stable

Incompatibility (materials to avoid)

Copper is potentially explosive with acetylinic compounds, 3-bromopropene, ethylene oxide, lead azide, and ammonium nitrate. Ignites on contact with chlorine, fluorine, and hydrazinemononitrate. Reacts violently with sodium azide, halogenates, peroxides, hydrogen sulfide, hydrozoic acid, bromates, chlorates, iodates, chloride and potassium oxide. Avoid contact with strong acids.

Hazardous Decomposition Products

High temperatures associated with smelting or welding releases metal oxide fumes.

Hazardous polymerization

Will not occur

11. TOXICOLOGICAL INFORMATION, CARCINOGEN STATUS:

Copper: The EPA has determined that copper is not classified to be known or to be a potential carcinogen, (cancer causing material).

Silver: The EPA has determined that silver is not classifiable as to human carcinogenicity.

Arsenic: The EPA has classified inorganic arsenic as a Group A, human carcinogen.

Antimony: EPA has not classified antimony for carcinogenicity.

Phosphorus: The EPA has determined that white phosphorus is not classifiable as to its carcinogenicity in humans. There are no studies available in people or animals that suggest white phosphorus causes cancer.

Tellurium: The EPA determined that Tellurium is not reported to be carcinogenic.

12. ECOLOGICAL INFORMATION

This material may be recyclable. Contact your Sales Representative.

13. DISPOSAL CONSIDERATIONS

MATERIAL DISPOSAL: Return metal to reclaimer. Collected dust from machining, welding, etc. might be considered "hazardous waste" in some circumstances. Consult local, state and federal authorities regarding disposal of this material.

14. TRANSPORTATION INFORMATION

DOT: Not regulated in solid form.

Hazard Communication regulations of the U.S. Occupational Safety and Health Administration require this product to be labeled.

15. REGULATORY INFORMATION

15.1. UNITED STATES FEDERAL REGULATIONS

15.1.1 Occupational Safety and Health Administration (OSHA)

Air contaminants, 29 CFR 1910.1000

Hazard Communication Standard, 29 CFR 1910.1200

15.2 Environmental Protection Agency (EPA)

AMBIENT AIR EMISSIONS: Most process air emission sources will require an air permit from a local and/or state air pollution control agency. The use of air cleaning equipment may be necessary to achieve the permissible emission. Tempered makeup air should be provided to prevent excessive negative pressure in a building. Direct recycling of cleaned process exhaust air is not recommended. Plant exhausts should be located so as not to re-enter the plant through makeup air or other inlets. Regular maintenance and inspection of air cleaning equipment and monitoring of operating parameters is recommended to ensure adequate efficiency is maintained.

WASTEWATER: Wastewater regulations can vary considerably. Contact your local and state governments to determine their requirements.

TOXIC SUBSTANCES CONTROL ACT: Component(s) of this material is/are listed on the TSCA Chemical Substance Inventory of Existing Chemical Substances

15.3 SARA TITLE III REPORTING REQUIREMENTS: On February 16, 1988, the U.S. Environmental Protection Agency (EPA) issued a final rule that implements the requirements of the Superfund Amendments and Reauthorization Act (SARA) Title III, Section 313 (53) Federal Register 4525. Title III is the portion of SARA concerning emergency planning and community right-to-know issues. Section 313 covers annual emission reporting on specific chemicals which are manufactured, processed or used at certain U.S. Industrial facilities.

Under the Section 313 category of Compounds and/or Mixtures, these mixtures contain one or more of the following reportable constituents: Copper, Chromium, Nickel, Beryllium, Cadmium, Cobalt, Lead, Iron, Silicon, and Aluminum.

Specific chemical makeup, concentration by weight and the Chemical Abstracts Services number for each of our products is provided in Section 3. You may obtain additional information by calling the EPA SARA Title III Hotline at 1-800-535-0202 (or 703-412-9810).

16. OTHER INFORMATION

Following is the label which accompanies this product during shipment.

This material data sheet (MSDS) provides information on a specific group of manufactured metal products. Since these metal products share a common physical nature and constituents, the data presented are applicable to all alloys identified.

This information was obtained from current and reputable resources. However, data are provided without warranty, expressed or implied, regarding correctness or accuracy. It is the user's responsibility both to determine safe conditions for use of this product and to assume liability for loss, injury, damage or expense resulting from improper use of this product.